



VICTORIA

Manufactured in Victoriaville, PQ and Kensington, PE



Recommended Overlap Procedure



FINISH	MATERIAL GAUGE				LENGTH
	30	28	26	24	
GALVALUME	•	•	•		4' to 32'
GALVANIZED	•	•	•	•	4' to 32'
PRE-PAINTED	•	•	•	•	4' to 32'

STEEL:

- Galvanized and Galvalume
- Pre-painted Galvanized WeatherXL™ series (see Vicwest standard colors).



APPLICATION - Walls and Roofs

MATERIAL SPECIFICATIONS:

The steel used in the manufacture of VICTORIA sheet meets the following specifications:

- ASTM A653 (latest revision) Structural Steel Grade 33 for all thicknesses, with designation G90.
- ASTM A792 (latest revision) Structural Steel Grade 33
 - for Galvalume, with designation AZ50 (AZM150)
 - for Galvalume Plus, with designation AZ50 (AZM150)
 - for Galvalume Plus, with designation AZ180

VICTORIA is without a doubt one of the most economical profiles that you can use on roofs and walls of existing and new farm buildings. Furthermore, Victoria has proven over many years its reliability and durability, with its triple protection side lap and its reversible design. Consequently, VICTORIA can fulfill all your agricultural cladding needs.

Minimum recommended slope: 4/12

Recommended nailing centres: 16" (406mm)

Flattening on the top of the main ribs provides for ease of nailing.

This profile can be curved: Concave and convex