


CL 439

Manufactured in Delta, BC



| FINISH                 | MATERIAL GAUGE |    |    | LENGTH    |
|------------------------|----------------|----|----|-----------|
|                        | 26             | 24 | 22 |           |
| GALVALUME              | •              | •  | •  | 6' to 35' |
| GALVANIZED             | •              | •  | •  | 6' to 35' |
| PRE-PAINTED GALVANIZED | •              | •  | •  | 6' to 35' |

STEEL:

- Galvanized and Galvalume
- Pre-painted Galvanized WeatherXL™ series (see Vicwest standard colors).



MATERIAL SPECIFICATIONS:

The steel used to manufacture CL 439 sheet meets the following specifications:

- ASTM A792 Grade 33 (latest revision) with designation AZ50 (AZM150) for Galvalume material.
- ASTM A653 SS, Grade 33 (latest revision) with designation Z275 for Galvanized material.
- ASTM A653 SS, Grade 33 (latest revision) with designation Z180 or Z275 for pre-painted Galvanized material.

For a more subdued shadow effect, Vicwest's CL 439 panel is an ideal choice. The narrow 1 3/8" deep ribs are spaced at 13 1/8" centre to centre. This pattern creates a subtle refined shadow line which will enhance the appearance of your project.